

FEATURES ↘

- 11 Selectable units of Measure
- Max/min/average, and with a relative time
- Large LCD backlit dual display
- Zeroing, offset, and data compensation
- Low battery display and automatic shutdown
- Data Hold and Error code



ET-922		ET-923		ET-925	
Range	Resolution	Range	Resolution	Range	Resolution
±415.2	0.1	±830	1	±2078	1
±15.00	0.01	±30.00	0.01	±75.00	0.01
±1034	1	±2068	1	±5168	1
±103.4	0.1	±206.8	0.1	±517.1	0.1
±30.54	0.01	±61.08	0.01	±15.00	0.01
±775.7	0.1	±1551	1	±3878	1
±240.0	0.1	±480.0	0.1	±1200	0.1
±34.60	0.01	±69.20	0.01	±137.0	0.01
±1055	1	±2109	1	±5272	1
±1.055	0.001	±2.109	0.001	±5.250	0.001
±1.034	0.001	±2.068	0.001	±5.138	0.001
100		100		100	
±0.3%FS (25°C)					
±0.2%FS (Max0.5%FSO)					
0.29%FSO					
1/8" (3.18mm) quick connector					
0 ~ 40°C/32 ~ 104°F					
-10 ~ 60°C/14 ~ 140°F					
ERR1 or ERR2					
9V					