

# iProbe Plus Scanning Probe



Secure data storage, reporting, and traceability in the palm of your hand.



## Key Features

- Filter scan report traceability
- On-board data storage
- Easy data transfer via USB
- Large, 4.3-inch color touchscreen
- Compatible with existing 2i photometers, no firmware update required ("plug and play")\*
- Optional password protection

## Key Benefits

- Supports 21 CFR Part 11 compliance
- Enhances data integrity and quality control
- Eliminates the need to connect to a computer or printer for real-time data output
- Improves efficiency and saves time

\* 2i main unit must be at firmware rev 4.6.1 or higher



# IProbe Plus Scanning Probe

## Quality Control, Traceability, and Security

The iProbe **Plus** creates a unique record of each filter scanned. Each record includes key identifiers (IDs) and important scan data for quality control and leak scan traceability.

### Scan Traceability IDs

### Additional Data for Each Scan

- Job
  - Room
  - Filter
  - Technician
  - Max % leakage
  - Effective scan time
  - Every alarm instance recorded
  - Pass/fail recorded for each scan
- **Supports 21 CFR Part 11 compliance** through encryption, password protection, and data protection. Filter leak data saved on the iProbe Plus cannot be altered.
  - Offers optional **password protection** of critical parameters such as date/time, deletion/removal, and **encryption** of the test data.
  - **Reporting:** Can save approx. 150,000 scans. Each saved leak scan is in a **.CSV and .PDF** file format for easy analysis. The files can be removed via a USB-A stick.

## Efficiencies, Ease of Use, and Safety

### Upstream/Downstream/Clear Controls:

The iProbe **Plus** allows the user to actuate the upstream/downstream/clear valves through the touchscreen (patented feature). This improves efficiency and safety by eliminating the need to actuate the valves through the 2i base unit.


### Additional User Conveniences:

- All firmware updates are installed via USB-A memory stick
- Unique 10-second "rewind" button allows the exclusion of accidental alarm events (patent pending)
- Ergonomic handle with finger grooves and thumb rest
- Important information displayed on screen, such as Max % Leakage; Filter ID; Elapsed Scan Time


Item Description	Part Number
iProbe Plus (only)	9300538
iProbe Plus / 2i small ensemble (120V)	9300529
iProbe Plus / 2i small ensemble (240V)	9300530



Scanning Screen



Scan Traceability IDs



Security Settings



Ergonomic Handle



Scan for more details and a video demonstration



Protecting People, Products & Critical Infrastructure

REV A

USA +1 410.363.9696  
UK +44 (0) 1462 676446

info@atitest.com  
www.atitest.com

